HSF

NOTES:
Current Rating: 3.0AMP
Contact Resistance: 20mΩ Max
Withstand Voltage: 1000V AC/DC
Insulation Resistance: 1000MΩ Min
Operation Temperature: −40℃ to +105℃

Contact Material:Phosphor Bronze
Contact plating:Au Or Sn over Ni
Insulator Material:PA9T+30%G.F UL94V-0



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Ordering Information

2171T - 2 XX M XX GUN X X

- XX: No.of Pins per ROW:02~40PIN
- XX: Contact Plating:
  G0=Gold Flash
  G3=10μ"Gold
  G4=15μ"Gold
  G5=30μ"Gold
  S0=Gold Flash/Tin
  S3=10μ"Gold/Tin
  S4=15μ"Gold/Tin
  S5=30μ"Gold/Tin
  SN=Tin
  SM=Matte Tin
- X: Packing:
  T=Tube
  P=Tube+CAP
  R=Tube&Reel+CAP
- X: Series No.
  1=TYPE 1
  2=TYPE 2





TYPE 2 WITH POST



TYPE 1 W/O POST

Item	Pitch	Mating
Standard	2.54	1115/1120/1125
Alternate		

TITLE	PART NO. A1
TYPE 1	2171T-2XXMXXGUNX1
TYPE 2	2171T-2XXMXXGUNX2

REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A1	2014/04/25	Modify drawing	------
A0	2012/08/13	NEW	------

OPERATION	
X.X	±0.40
X.XX	±0.25
X.XXX	±0.15
Angle	± 3°
DIM	TOL

DRAW: Wang — DATE: 2014/04/25
CHECK — DATE
APPROVE — DATE

SCALE: FIT
UNIT: mm
SIZE: A4
SHEET: 1/1
PROJ.:

PART NO.: SEE TABLE
TITLE: FH2.54 DUAL ROW 180° SMT H=7.25
Customer NO.

WCON
Http: www.wcon.com
WCON-Dongguan
Tel: +86 769 85358920
Fax: +86 769 85358915
E-mail: sales@wcon.com
WCON-Kunshan
Tel: +86 512 57468408
Fax: +86 512 57468468
E-mail: salesks@wcon.com